

| Models /Specifications | | | | |
|---|--|--------------|--|---|
| Model | Bubbler | Check Valve* | Swing Assembly w/ ½" (15/21) M NPT inlet | Spiral Barb Elbow w/ ½" (15/21) M NPT inlet |
| 36" Root Watering System (with 4" (10.2 cm) vandal-resistant locking grate) | | | | |
| RWS | Ideal for ¼" drip tubing or customer provided hardware | – | – | – |
| RWS-B-C-1401 | 0.25 gpm (0.95 l/m) | ✓ (36") | ✓ | – |
| RWS-B-1401 | 0.25 gpm (0.95 l/m) | – | ✓ | – |
| RWS-B-X-1401 | 0.25 gpm (0.95 l/m) | – | ✓ (18" with no elbow) | – |
| RWS-B-C-1402 | 0.50 gpm (1.9 l/m) | ✓ (36") | ✓ | – |
| RWS-B-1402 | 0.50 gpm (1.9 l/m) | – | ✓ | – |
| RWS-B-C-1404 | 1.00 gpm (3.8 l/m) | ✓ (36") | ✓ | – |
| 18" Root Watering System - Mini (with 4" (10.2 cm) vandal-resistant locking grate) | | | | |
| RWS-M | Ideal for ¼" drip tubing or customer provided hardware | – | – | – |
| RWS-M-B-C-1401 | 0.25 gpm (0.95 l/m) | ✓ (18") | – | ✓ |
| RWS-M-B-1401 | 0.25 gpm (0.95 l/m) | – | – | ✓ |
| RWS-M-B-C-1402 | 0.50 gpm (1.9 l/m) | ✓ (18") | – | ✓ |
| RWS-M-B-1402 | 0.50 gpm (1.9 l/m) | – | – | ✓ |
| 10" Root Watering System - Supplemental (with 2" (5.1 cm) snap-on cap and base) | | | | |
| RWS-S-B-C-PCT5 | 5.0 gph (19 l/m) | ✓ (10") | – | ✓ |
| RWS-S-B-C-1401 | 0.25 gpm (0.95 l/m) | ✓ (10") | – | ✓ |
| RWS-S-B-1401 | 0.25 gpm (0.95 l/m) | – | – | ✓ |
| Root Watering - Accessories | | | | |
| RWS-SOCK (Root Watering Sock) | | | | |
| RWSGRATE (Root Watering System Black Grate for RWS and RWS Mini) | | | | |
| RWS- GRATE-P (Root Watering System Purple Grate for RWS and RWS Mini) | | | | |

* Check Valve is 14 ft. of holdback, or 6 PSI

